

5. OTIS·LG

HILGEN

| | (kW) | | | |
|-------|--------------------|-----------------|-------------|------------|
| | 4P | | 6P | |
| | VX | VY | VX | VY |
| 112 S | 0.75 1.5 2.2 | 0.75 1.5 | 0.75 1.5 | 0.75 |
| 112 M | 3.7 | 2.2 | 2.2 | 1.5 |
| 132 S | 5.5 | 3.7 | 3.7 | 2.2 |
| 132 M | 7.5 | - | 5.5 | 3.7 |
| 160 M | 11 | 5.5 | 7.5 | 5.5 |
| 160 L | 15 | 7.5 11 15 | 11 | 7.5 |
| 180 M | 18.5 | 18.5 | 15 | 11 |
| 180 L | 22 | 22 | 18.5 | 15 |
| 200 L | 30 37 | 30 37 | 22 | 18.5 22 |
| 225 M | 45 55 | 45 55 | 30 37 | 30 37 |
| 250 M | 75 | 75 | 45 55 | 45 55 |
| 280 S | 95 | - | 75 | - |
| 280 L | 110 132 150 | - | 95 110 | - |
| 315 M | 185 | - | 132 150 | - |

| | (kW) | | | |
|-------|-------------------------------|------------------------|-----------------------------|------------------------|
| | 4P | | 6P | |
| | VX | VY | VX | VY |
| FF215 | 0.75 1.5 2.2 | 0.75 1.5 | 0.75 1.5 | 0.75 |
| FF215 | 3.7 | 2.2 | 2.2 | 1.5 |
| FF265 | 5.5 7.5 | 3.7 | 3.7 5.5 | 2.2 3.7 |
| FF300 | 11 15 | 5.5 7.5 11 15 | 7.5 11 | 5.5 7.5 |
| FF350 | 18.5 22 | 18.5 22 | 15 18.5 | 11 15 |
| FF400 | 30 37 45 55 | 30 37 45 55 | 22 30 37 | 18.5 22 30 37 |
| FF500 | 75 95 110 132 150 | 75 | 45 55 75 95 110 | 45 55 |

OTIS·LG